



2-PRONG PUSH-DOWN IMPALER CLIPS

MetroFlex 2-Prong PushDown Impaler Clips are designed to make fastening Acoustic Panels to walls fast and easy. MetroFlex PushDown Impaler Clips are made from galvanized steel and contain 2 angled pronges per clip. The PushDown clips are designed to work with both Fiberglass and Mineralwool Panels with densities from 3 to 8 lbs/cf. The prongs can pierce most facings including ASJ or FSK.

Recommended Installation

A minimum of 4 MetroFlex Impaling Clips should be used per acoustic panel. A standard 24" x 48" panel will require 4 clips while a 48" x 96" panel will require 12-16 clips.

Temporarily hold the acoustic panel in place on the wall and lightly mark the placement of the panel with pencil.

Measure approximately 4 inches inside from each edge of the panel to determine the location of the clips.

The PushDown Clips have a hole in the center and edges for fastening to the wall. Use a standard wood screw if the clip falls on a wood wall stud, a self-drilling metal screw if wall contains steel studs, or a drywall expanding screw if it does not fall on a stud. (Fasteners not included)

Once all clips are installed, hold the panel over the clips and with the use of a level, firmly press downward and impale the acoustic panel onto the clips.

*Warning: On lighter density panels and thinner panels, be careful of the impaling prongs.

For a permanent installation, beads of construction grade adhesive caulking can be applied to the wall before impaling the panel onto the clips. Not recommended for use on ceiling installs.



Packaging Information

24 Impaling Clips / Box

Impaling Clip Dimensions

3" x 1-1/2" Base
2 Angled Spikes (1" Long)
3 Fastener Holes



- Installing Acoustic Panels to Walls Has Never Been So Easy -